


Sun Odyssey 44i



Certification conform with CE regulation.

SO 44i

SPECIFICATIONS	
Overall length	13,75 m
Hull length	13,41 m
Waterline length	11,45 m
Beam	4,37 m
Displacement light load with deep draft keel	9930 kg
Standard draft cast iron fin keel with elongated bulb and exterior epoxy barrier coat	2,05 m
Standard keel weight	2954 kg
Shoal draft cast iron fin keel with elongated bulb and exterior epoxy barrier coat	1,65 m
Shoal keel weight	3160 kg
CE category	A10-B12-C14
Architect / Designer	P. Briand
Water 2 rotomolded tanks located under forward and aft berths with separate deck fills	615 L
Fuel rotomolded tank located under aft berth with deck fill	240 L
Holding tank rotomolded tank located in head compartment with valve for overboard discharge via gravity and deck fitting for pump out	85 L
Fridge fibreglass fridge compartment with 2 separate compartments and vertical access	255 L
SAILS	
Classic mainsail 80% battened, high-tenacity Dacron cloth, Rutgerson® stainless steel eyes and 2 auto reefs	47,6 m²
Furling genoa 140% high-tenacity Dacron cloth, Sunbrella® UV luff protection, Rutgerson® stainless steel eyes	53 m²
Furling mainsail (optional) high-tenacity Dacron cloth, Sunbrella® UV luff protection, Rutgerson® stainless steel eyes	36,9 m²
Spinnaker optimal size for boat (not available from Jeanneau)	120 m²
Total sail area for standard mast and sails	100,6 m²

■ Standard □ Option

SAIL HANDLING

Lazy bag in Sunbrella® Taupe fabric with integrated lazy jacks	■
Genoa winches 2 x Harken 50.2 self-tailing winches	■
Coachroof winches 2 x Harken 46.2 self-tailing winches	■
Electric genoa winches 2 x Harken 50.2 STCE-H 12v self-tailing in place of standard winches	□
Electric coachroof winch 1 x Harken 46.2 STCE-H 12v self-tailing in place of standard winch to port	PREFERENCE
Genoa tracks adjustable Harken lead cars	■
Winch handles 2 x Harken handles with ball-bearing grip	■
Line jammers Spinlock, on both sides of coachroof with Harken return blocks	■
Mainsheet traveller long, roof-mounted Harken traveller with ball-bearing cars, control lines lead aft to cockpit	■
Padeyes 3 Wichard on each side for spinnaker turning blocks, tweaker lines, pole downhaul	■
Spinnaker deck hardware triple Spinlock jammer to starboard, and an additional 3-sheave return block on deck	■
Asymmetrical spinnaker gear halyard, 2 sheets, tack line lead forward on deck, reinforced fitting on anchor roller, 3 Harken blocks	□
Symmetrical spinnaker gear halyard, 2 sheets, 2 guys, pole uphaul and downhaul, spinnaker pole and adjustable car for mast, Harken blocks	□

MAST AND RIGGING

Classic mast aluminium with double spreaders, spinnaker track mounted forward and folding mast steps	■
Furling mast	□
Standing rigging discontinuous 1x19 stainless steel wire	■
Backstay fixed, double	■
Genoa furler with attachment to stemhead fitting and furling line lead aft to roof winch	■
Running rigging polyester topping lift, mainsail halyard, genoa halyard, mainsheet, genoa sheets	■
Rigid boom vang with gas cylinder and control line lead aft to the cockpit	■
Releasable forestay for storm sail, attaches to padeye in front of the anchor locker, stay is equipped with quick release and adjustment mechanism, inner stay is attached to a padeye on starboard side deck when not in use	□

COCKPIT & DECK STORAGE

Teak inlay on seating area, transom and transom steps	■
Teak cockpit floor inlay	□
Teak side decks hand-laid teak side decks	□
Cockpit lockers 2 lockers under bench seats and 2 lazette lockers under the helm seats for technical access to steering system	■
Cockpit table folding injected fibreglass table with storage, cup holders, bottle holders, stainless steel handrail, courtesy lighting, 12v plug, table base provides light, headroom and ventilation to aft cabins	■
Teak cockpit table with all the same functions of above, standard table but with teak leaves and top, Sunbrella® Taupe cover	□
Gas locker located outboard of port helm, room for 2 gas bottles with connection to gas system and cut-off valve under stove in the galley	■
Large storage locker under cockpit floor (location for optional generator)	■
Wheels 2 leather-covered steering wheels with fibreglass pedestals with handrail, cup holders, compasses and easy access to winches	■
Steering wheel covers Sunbrella® Taupe with zips for easy removal	□
Transom gate double fibreglass doors that can be secured when open or closed	■
Instrumentation dedicated space for instruments within easy reach of helm positions, room for GPS chartplotter mounted at aft end of cockpit table with easy viewing from each helm	■
Engine controls throttle and engine control panel mounted at starboard helm, engine panel, RPM gauge, warning lights, ignition	■
Swim ladder stainless steel folding ladder mounted on swim platform	■
Cockpit shower retractable hot and cold water shower with tap	■
Cockpit cushions Sunbrella® Sling Taupe cushions for seating area with attachment clips	□
Cockpit bimini Sunbrella® Taupe with stainless steel bows, retractable with storage cover	□
Cockpit sprayhood wide Sunbrella® Taupe with vinyl windscreen with zip-out middle window for ventilation, retractable	□
Anchor locker forward, lockable, room for anchor and tackle, integrated windlass area, holder for windlass handle	■

DECK HARDWARE

Short Performance bow pulpit stainless steel	■
Stern pulpits stainless steel with flag holder, buoy bracket	■
Outboard engine bracket mounted on stern pulpit	□
Windlass Quick 1000W combination rope and chain 10mm, vertical-mounted in the anchor locker, hand-held remote, manual handle	■
Windlass control second windlass control mounted in cockpit with chain counter for easy, short-handed anchoring	□
Anchor roller double stainless steel fitting with self-launching roller for hands-free launching and retrieving	■
Anchoring kit Delta anchor 20kg with 32 meters of 10mm chain and 45 meters of 18mm line	□
Lifelines double level of stainless steel lifelines with PVC coating, stainless steel stanchions with open gates	■
Toerail teak profile with integrated stainless steel chocks and drainage for side deck	■
Cleats 6 x aluminium mooring cleats	■
Rubrail for hull protection	□
Mooring kit fenders and docklines	□
Handrails sculpted, long teak handrails on coachroof for secure movement forward	■

■ Standard □ Option

TECHNICAL FEATURES AND OPTIONS

CONSTRUCTION

Deck Prisma Process® injected deck, ISO gelcoat surface, discontinuous balsa block coring	■
Hull solid, hand-laid fibreglass, ISO gelcoat surface, protective barrier coat	■
Structure 3 rd generation counter-moulding, high-load zones cut out and relaminated, drainage system through structure, special emergency repair zone in keel area	■

LIGHTING

LED navigation lights and anchor light	PREMIERE
Flush mounted chromed brass LED ceiling lights in saloon, head compartments and cabins	■
On/off switches in saloon for overhead lights	■
Indirect LED lighting under side decks in saloon	■
Red/white combination light for night vision at nav station	■

ELECTRICAL CIRCUIT

12v alternator output	80 A
Charge distributor/isolator	■
Engine start battery capacity	110 Ah
Domestic battery bank capacity	330 Ah
Extra 110 Ah domestic battery	PREMIERE
Positive battery switch for engine bank, positive battery switch for domestic bank and negative general cut-off switch	■
220v shore power inlet with differential breaker	■
60A Cristec battery charger, multi-phase	PREMIERE
Electrical panel with 12v breakers, 220v breakers, LCD display with 12v voltmeter, 12v consumption meter, fuel and water tank gauges	■
One 220v and 12v plug per cabin, 220v plugs in galley, saloon and nav station	■
220v stainless steel microwave	□
Generator 6 kw ONAN 220v located in fully-soundproofed, locker below cockpit floor, power selector switch and generator control panel located at nav station, exhaust separator with below waterline discharge for silent operation	□

PLUMBING

Hot and cold pressurised water distributed through-out the boat via semi-rigid hose	■
"Heavy-duty" water pump and accumulator tank for consistent water pressure	■
40 litre hot water tank that is connected to engine heat exchanger and to 220v electrical system	■
Chromed shower faucets in washrooms	■
Shower sumps equipped with individual electric pumps and on-off switches	■
Large manual pump marine toilets	■
Jabsco electric Quiet-Flush toilets in place of standard, available for each head compartment	□
85 litre holding tank with gravity drain and deck fitting for other head compartments (port aft head equipped with standard tank), available for each head compartment	□

ENGINE

Yanmar 4JH5-CE 54 HP Sail Drive , 39.6Kw latest generation of environmentally friendly engines	■
360 Docking System - Yanmar 4JH4 TE POD 120 engine with pivoting sail drive unit and joystick (includes bow thrusters and autopilot)	□
Fully soundproofed engine compartment with engine access behind stairwell and from aft cabin	■
Fuel/water separator	■
Built-in muffler, forced air ventilation and stainless steel exhaust fitting aft	■
Fixed 3-blade bronze propeller	■
Flex-o-fold folding propeller	□
Bow thruster Map-Power composite mounted in tunnel with additional battery and control at starboard helm	□

COMFORT

Fixed hull ports with track-mounted curtains	4
Opening cockpit and roof ports with curtains	6
Opening deck hatches forward-facing with sun blinds integrated into headliner	9
Insect screens for each deck hatch, integrated into headliner	■
CD/radio/MP3 player in saloon	■
BOSE® 2.1 speaker system ACCOUSTIMASS 3, speakers with base unit in saloon	PREMIERE
Cockpit speakers watertight	PREMIERE
TV LED 20" mounted on an articulating arm on main saloon bulkhead to port of the forward cabin doorway	□
DVD player in saloon (replaces standard CD player)	□
Air Conditioning 220v 24000 BTU 2 units with digital controls and vents in saloon, forward and aft cabins	□
Forced air heating 1 unit 5500 BTU Webasto® diesel heater installed in cockpit lazarette, vents in aft cabin, saloon and head compartments	□

■ Standard □ Option

	SO 44i		
	3C/2H	3C/3H	4C/2H
I N T E R I O R			
WOOD			
Fine Teak® interior laminated panels with solid wood trim around galley, companionway and cabinetry, finished in satin UV stabilised varnish	■	■	■
Laminate floorboards with light-coloured lines, varnished edges	■	■	■
PREMIUM mattresses available on all berths, provides the ultimate in comfort	■	■	■
FORWARD OWNER'S CABIN			
Forward owner's cabin with central berth and reading lights at head of berth	■	■	■
Double berth with trim, PREMIUM mattress	2,00-1,50 m	2,00-1,50 m	-
Mattress battens under high-density foam mattress for increased comfort	□	□	-
Cushioned seat	■	■	-
Storage under berth	■	■	-
Large hanging locker	■	■	-
Vanity in forward cabin with desk, mirror, and lighting	■	■	-
Wood and white upholstered panels along hull	■	■	-
Storage lockers along hull sides with gas lifters and indirect lighting underneath	■	■	-
Private forward owner's head compartment with sink, separate shower with plexiglass door, mirror, towel holder, toilet paper holder, wastebasket, cabinet above sink and shower sump with grate and electric drainage pump	■	■	-
Twin forward cabins transformable into single cabin by removable longitudinal bulkhead	-	-	■
Double berths, PREMIUM mattresses	-	-	2,02 m-1,35 m
Storage under berth	-	-	■
Hanging lockers	-	-	■
Storage lockers along hull sides with gas lifters and indirect lighting underneath	-	-	■
Bunk beds in forward cabin, removable	-	-	□
Fabric hull liner	-	-	■
TWIN AFT CABINS			
Twin aft cabins	■	■	■
Double berths, PREMIUM mattresses	2 x 2,02 m-1,5 m	2 x 2,02 m-1,5 m	2 x 2,02 m-1,5 m
Deep cabinet with shelves and hanging rod per cabin	■	■	■
Storage compartments along hull with indirect lighting underneath and open hanging lockers to either side of berth	■	■	■
Wood and white upholstered panels along hull	■	■	■
Head compartment aft with sink, shower, mirror, towel holder, toilet paper holder, wastebasket, shower sump, with grate and electric drainage pump, access from aft cabin and saloon	■	-	-
2 head compartments aft with sink, shower, mirror, towel holder, toilet paper holder, wastebasket, cabinet above sink and shower sump with grate and electric drainage pump access from aft cabins and saloon	-	■	■
NAVIGATION STATION			
Navigation station full-function with general electrical panel	■	■	■
Lateral navigation desk with cushioned stool	-	■	■
Navigation desk with roll-away top and pass-through for plugs to facilitate the use of a laptop computer	■	-	-
Large storage drawer with divider under nav station/bar cabinet	■	-	-
SALOON			
Saloon with U-shaped seating area to starboard, wrap-around cushions and storage under seating area	■	■	■
Saloon dining table with fiddles, removable pedestal legs and built-in bottle locker	■	■	■
Split cushion to fit over saloon table and support to turn standard table into a double berth	□	□	□
Deluxe saloon table with fixed storage base, inlaid table top, and folding leaves	□	□	□
Fixed bench seat facing table with cushion and leather-wrapped handrail	□	□	□
2 removable luxury armchairs with tiedowns for saloon (instead of bench seat)	□	□	□
Upper storage cabinets	■	■	■
Storage cabinet along hull	■	■	■
Indirect lighting under sidedecks	■	■	■
Companionway made of laminate and solid wood trim with curved, hinged for access to engine, leather-wrapped handrails to either side	■	■	■
GALLEY			
Galley with double sinks with covers and reversible cutting board, solid surface countertops, chrome plumbing fittings, storage cabinets and drawers	■	■	■
Longitudinal galley	■	■	■
Dish draining compartment with cover	■	■	■
Gimballed 2-burner stove with oven with stainless steel protection bar	■	■	■
3-burner stainless steel stove with thermostatically controlled oven and stainless steel protection bar, in place of regular stove/oven unit	PREMIERE	PREMIERE	PREMIERE
Double fridge box, top-loading with 2 opening lids, storage bins, 12v refrigeration and gas lift for door in large box and compressor	■	■	■
12v freezer unit for smaller fridge box with separate compressor	PREMIERE	PREMIERE	PREMIERE
Stainless steel vertical access door to large fridge box, includes wire shelving inside fridge box for increased storage	PREFERENCE	PREFERENCE	PREFERENCE
H E A D R O O M			
Forward cabin (s)		1,90 m	
Aft cabin (s)		1,95 m	
Companionway		1,95 m	
Saloon		1,93 m	
Galley		1,92 m	

■ Standard □ Option - Not available C = Cabins H = Head



JEANNEAU

Ets JEANNEAU - BP 529 - 85505 LES HERBIERS CEDEX - FRANCE - TEL +33 (0)2 51 64 20 20 - FAX +33 (0)2 51 67 37 65

INTERNET : <http://www.jeanneau.com>

